

## **DECLARATION OF PERFORMANCE**

According to Regulation CPR EU N° 305/2011

DoP N°: **004** 

1. Unique identification code of the product-type:

PRESTIGE TRADITIONAL

2. Intended use/uses:

Bitumen shingles with mineral reinforcement, for roof and external wall covering (EN 544:2011, Type 4 X 8)

Manufacturer:

Tegola Canadese S.r.l.

via dell'Industria, 21 - 31029 - Vittorio Veneto (TV) - Italia tel: +39 0438 9111 mail: info@tegolacanadese.com

4. Authorised representative:

Not applicable

5. System/s of AVCP:

System 4 - for all properties, except Reaction to Fire and External Fire Resistance System 3 - for Reaction to Fire and External Fire Resistance

6. a) Harmonized standard:

EN 544:2011

Notified Body/ies:

CSI S.p.a. - Bollate (MI) - Italia, Organismo Notificato N° 0497- for Reaction to Fire and External Fire Resistance

7. Declared performances:

| Essential Characteristics                  | Unit of<br>Measure | Performance |    | Harmonized standard |
|--|--------------------|-------------|----|---------------------|
| Mechanical Resistance:                     |                    |             |    |                     |
| - Tensile Strength (Width)                 | N/50mm             | ≥ 850       |    |                     |
| - Tensile Strength (Height)                | N/50mm             | ≥ 510       |    |                     |
| - Nail Shank Tear Resistance               | N                  | ≥ 150       |    |                     |
| Reaction to Fire                           |                    | C, s2, d0   |    | 7                   |
| External Fire Resistance                   |                    | Broof(t1)   |    | 1                   |
| Water Permeability (Mass of Bitumen)       | g/m²               | ≥ 1300      |    |                     |
| Dimensional Variation:                     |                    |             |    | 7                   |
| - Width                                    | mm                 | 1000        | ±3 | EN 544:2011         |
| - Height                                   | mm                 | 340         | ±3 |                     |
| Durability of Mechanical Resistance        | -                  | Pass        |    | 7                   |
| Durability of Water Permeability           |                    |             |    | 7                   |
| - Flow Resistance at Elevated Temperatures | mm                 | <1          |    |                     |
| - Resistance to Peeling                    | N/5cm              | >5          |    |                     |
| - Water Absorption                         | %                  | <1          |    |                     |
| Resistance to Fixing                       | N                  | ≥ 150       |    |                     |
| Dangerous Substances                       | -                  | NPD         |    | 7                   |

8. Appropriate technical documentation and/or specific technical documentation:

Not applicable

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) N° 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

Vittorio Veneto, 10/04/2013

Rev. 02, 18/01/2024

Chiara Mazzer
President and CEO

Via dell'Industria, 21 31029 VITTORIO VENETO (TV Tel. 0438 9111 r.a. Cod. Fisc. - Part. IVA 0044993026